

Ivybrook Academy Valley Ridge

10660 US Highway 1 N Ste 103
Ponte Vedra Beach, FL

1 Inspection Visit Since 2026 · 1 Finding

Most recent inspection: Apr 22, 2026

● 1 Important

Across 1 inspection since 2026, the issues cited most often were The Ground Cover or Other Protective Surface Under the [Outside Equipment That Children Climb on] Was Not Maintained. CCF Handbook, Section 3.12, D

Resilient Surface Under and Around Structures That Children Climb on Was Not 6 Inches Deep. Fall Zone Resilient Surface Must Be 6 Ft in All Directions From the Perimeter and 6 Inches Deep. 3.12 Outdoor Equipment Page 38-39 D. Permanent or Stationary Playground Equipment Must Have a Fall/use Zone That Extends a Minimum of 6 Feet in All Directions From the Perimeter of the Equipment. All Types of Ground Cover Must Be Maintained to Provide Resilience and Reduce the Incidence of Injuries to Children in the Event of Falls. 1. If the Ground Cover in Place Is Loose Ground Cover (Such As, but Not Limited To: Mulch, Shredded Rubber Chips, or Sand) a Minimum of 6 Inches in Depth Is Required in the Use Zone. Asphalt, Concrete, Hard Packed Dirt, Hay, Grass or Leaves Are Unsuitable for Use in the Use Zone Area. 2. If the Ground Cover in Place Is a Unitary Playground Surface, Then the Unitary Surfacing Materials Must Be Installed, Maintained, or Replaced According to Manufacturers Instructions. Unitary Surfaces Must Be Tested to and Comply with ASTM F1292; Documentation of Test Data Must Be Retained at the Facility and Available for Licensing to Review. Due Date 5/13/2026 TRAINING (1). The single finding was not critical.

Inspection Visits

Apr 22, 2026 1 Finding ● 1 Important

About this report

Childery generates this report from public inspection records published by the Florida Department of Children and Families, Office of Child Care Regulation. Childery did not conduct these inspections or produce the original state reports. Childery is an independent directory and is not affiliated with the Florida Department of Children and Families, Office of Child Care Regulation.

- **The Ground Cover or Other Protective Surface Under the [Outside Equipment That Children Climb on] Was Not Maintained. CCF Handbook, Section 3.12, D**

Resilient Surface Under and Around Structures That Children Climb on Was Not 6 Inches Deep. Fall Zone Resilient Surface Must Be 6 Ft in All Directions From the Perimeter and 6 Inches Deep. 3.12 Outdoor Equipment Page 38-39 D. Permanent or Stationary Playground Equipment Must Have a Fall/use Zone That Extends a Minimum of 6 Feet in All Directions From the Perimeter of the Equipment. All Types of Ground Cover Must Be Maintained to Provide Resilience and Reduce the Incidence of Injuries to Children in the Event of Falls. 1. If the Ground Cover in Place Is Loose Ground Cover (Such As, but Not Limited To: Mulch, Shredded Rubber Chips, or Sand) a Minimum of 6 Inches in Depth Is Required in the Use Zone. Asphalt, Concrete, Hard Packed Dirt, Hay, Grass or Leaves Are Unsuitable for Use in the Use Zone Area. 2. If the Ground Cover in Place Is a Unitary Playground Surface, Then the Unitary Surfacing Materials Must Be Installed, Maintained, or Replaced According to Manufacturers Instructions. Unitary Surfaces Must Be Tested to and Comply with ASTM F1292; Documentation of Test Data Must Be Retained at the Facility and Available for Licensing to Review. Due Date 5/13/2026 TRAINING

32-07 - Outdoor Equipment CCF Handbook, Section 3.12

About this report

Childery generates this report from public inspection records published by the Florida Department of Children and Families, Office of Child Care Regulation. Childery did not conduct these inspections or produce the original state reports. Childery is an independent directory and is not affiliated with the Florida Department of Children and Families, Office of Child Care Regulation.